

# Infrared heater Standard ceiling



## STANDARD CEILING

500W  
60×90cm  
5.8kg/7.2kg\*  
white

VCIR-60-90-500

## STANDARD CEILING

700W  
60×120cm  
7.35kg/9.05kg\*  
white

VCIR-60-120-700

## STANDARD CEILING

350W  
60×60cm  
3.95kg/5kg\*  
white

VCIR-60-60-350

### Conformity:

EN 60335-1: 2012+A11  
EN 60335-2-30 : 2009+A11  
EN 62233 : 2008  
EN60601-1 : 2006  
EN60601-1 : 2001  
EN 6100.3.3.2013  
EN 61000.3.2.2014  
EN 60529 :1991+A1+A2

\* weight incl. packaging

**Infrapower® GmbH**  
Rudolf Hausner Gasse 3  
1220 Vienna  
www.infrapowerworld.com  
office@infrapowerworld.com  
Tel.: +43 (0) 1 734 1083

<b>Voltage</b>	230V/50Hz
<b>Overheating protection</b>	Integrated temperature sensors
<b>Protection class</b>	IP65
<b>Connection</b>	(3 × 0.75mm <sup>2</sup> ) Length 1.8m color white with „schuko plug“
<b>Control/Thermostat</b>	compatible with "Öko-design" conform units
<b>Abstrahlwinkel</b>	130° – 140°
<b>Strahlungswirkungsgrad</b>	Class I according to DIN EN60675/A2 VDE 0705-675/A2:2018-11
<b>Radiation array</b>	90%
<b>Color front/ frame</b>	Aluminum, coated, matt white
<b>Surface temperature front / rear at 22°C room temperature</b>	100° C / 50° C

# Standard ceiling

## Mounting and connections

